

TD40 shank (PM4.3) hammer



Features: _Length shank = 209mm / _12 Splines / _Height of Foot Valve above strike face = 57.0mm

Diameter		Code	Description	No. x Button diameter, mm (inch)				Flushing holes	Weight Approx.	
Inch	mm			Outer gauge	Inner Gauge	Front	Concavity		kg	Lbs
4 1/2"	115.00	020404000096	Dome Heavy	8x16 (5/8)	4x13 (1/2)	3x13 (1/2)		2	9,3	20,5
5"	127.00	020404000094	Dome Heavy	8x16 (5/8)	4x14 (9/16)	3x14 (9/16)		2	10,1	22,3
4 1/2"	115.00	0204040000101	Flat Face	8x14 (9/16)		8x13 (1/2)		2	9,3	20,5
4 1/2"	115.00	0204040000106	Flat Face Heavy A3	8x16 (5/8)		6x13 (1/2)		2	9,4	20,7
4 1/2"	115.00	0204040000105	Flat Face Heavy A2 B/S*	8x16 (5/8)		6x13 (1/2)		2	9,3	20,5
4 1/2"	115.00	0204040000104	Flat Face Heavy A1 Ballistic	8x16 (5/8)		6x13 (1/2)		2	9,4	20,7
4 13/16"	122.0	0204040000113	Flat Face Heavy B/S*	8x16 (5/8)		8x13 (1/2)		2	9,7	21,4
4 13/16"	122.0	0204040000114	Flat Face Heavy	8x16 (5/8)		8x13 (1/2)		2	9,7	21,4
5"	127.0	0204040000112	Flat Face Heavy Ballistic	8x16 (5/8)		8x13 (1/2)		2	10,1	22,3
5 1/8"	130.00	0204040000107	Flat Face	8x16 (5/8)		8x14 (9/16)		2	10,3	22,7
4 1/2"	115.00	020404000100	Drop Center	8x14 (9/16)		4x13 (1/2)	3x13 (1/2)	2	9,2	20,3
FOOT VALVE		0204060010013								

(*) : B/S = Ballistic Spherical (Spherical buttons on Outer Gauge and ballistic button on the other positions)

This information can be modified without notice of Drillco S.A. December 2017 (Modif. 0)