

DHD-350 shank (PM5.2, PM5.2EX) hammer



Features: _Length shank = 260mm / _8 Splines / _Height of Foot Valve above strike face = 63.0mm

Diameter		Code	Description	No. x Button diameter, mm (inch)				Flushing holes	Weight Approx.	
Inch	mm			Outer gauge	Inner Gauge	Front	Concavity		kg	Lbs
5 1/2"	140.00	0204050000032	Dome B/S*	8x16 (5/8)	4x16 (5/8)	3x16 (5/8)		2	16,0	35,3
5 1/2"	140.00	0204050000046	Dome Heavy	8x19 (3/4)	4x16 (5/8)	3x16 (5/8)		2	16,4	36,2
5 1/2"	140.00	0204050000063	Dome Welding	8x16 (5/8)	4x16 (5/8)	3x16 (5/8)		2	16,0	35,3
5 3/4"	146.00	0204050000066	Dome Heavy	8x19 (3/4)	4x16 (5/8)	4x16 (5/8)		2	16,6	36,6
5 1/2"	140.00	0204050000039	Flat Face "Quarry"	8x16 (5/8)		8x16 (5/8)		2	16,7	36,8
5 3/4"	146.00	0204050000013	Flat Face "Quarry"	8x16 (5/8)		8x16 (5/8)		2	17,6	38,8
5 1/8"	130.00	0204050000023	Concave	8x16 (5/8)		4x16 (5/8)	3x14 (9/16)	2	15,4	34,0
5 1/2"	140.00	0204050000001	Concave	8x16 (5/8)		4x16 (5/8)	3x16 (5/8)	2	16,6	36,6
5 3/4"	146.00	0204050000011	Concave "Quarry"	8x16 (5/8)		4x16 (5/8)	4x16 (5/8)	2	16,5	36,4
5 7/8"	149.00	0204050000022	Concave	8x16 (5/8)		4x16 (5/8)	3x16 (5/8)	2	16,9	37,3
FOOT VALVE		0204050010000								

(*): B/S = Ballistic Spherical (Spherical buttons on Outer Gauge and ballistic button on the other positions)

This information can be modified without notice of Drillco S.A. October 2017 (Modif. 0)